



# ECO-A2L

Two stage  
vacuum pumps

## FEATURES AND BENEFITS

- A2L suitable
- Compact design with aluminium housing and easy to grip carrying handle
- Very quiet operation
- High pumping capacity reduces evacuation time
- Both 1/4" and 3/8 " SAE flare inlet connections allow for flexibility of connections



VERSION	FREE AIR DISPLACEMENT	PART NO
ECO-3-A2L	84 l/min	4688854
ECO-5-A2L	142 l/min	4687805
ECO-9-A2L	254 l/min	4688853



# DATA SHEET

	<b>ECO-3-A2L</b>	<b>ECO-5-A2L</b>	<b>ECO-9-A2L</b>
<b>VOLTAGE</b>	230 V / 50/60 Hz	230 V / 50/60 Hz	230 V / 50/60 Hz
<b>FREE AIR DISPLACEMENT</b>	84 l/min (3.0 CFM)	142 l/min (5 CFM)	254 l/min (9 CFM)
<b>ULTIMATE VACUUM</b>	15 microns	15 microns	15 microns
<b>MOTOR</b>	0.25 kW	0.37 kW	0.74 kW
<b>INTAKE FITTING</b>	1/4" + 3/8" SAE	1/4" + 3/8" SAE	1/4" + 3/8" SAE
<b>OIL CAPACITY</b>	250 ml	325 ml	590 ml
<b>DIMENSIONS</b>	315 x 124 x 240 mm	335 x 140 x 250 mm	406 x 152 x 279 mm
<b>NET WEIGHT</b>	8.6 kg	10.4 kg	16.8 kg
<b>PART NO.</b>	4688854	4687805	4688853